



Quick Charger QM16

Fit for a Global Charge.

Refuel & Go, Quickly: PD & QC3.0

The QM16 delivers up to 20W of fast charge power with QC3.0 via the USB Type-A port and Power Delivery (PD) via the Type-C port. The two different outputs offer greater versatility to refuel mobile phones, tablets, and more. Plus, charge most mobile phones from 0% up to 50% in just 30 minutes!



20W

PD USB Type-C

QC3.0 USB Type-A

Charge In More Than 150 Countries

Due to its universal 100-240 input voltage, the QM16 is calibrated to handle a wide range of voltages. In addition, it includes attachable EU, UK, and AU plug adapters. With these simple snap-on converters at hand, the QM16 is truly travel-ready for charging compatibility in more than 150 countries.



Wall Charger QM16

Features

- Delivers up to 20W of charging power via the USB Type-A and Type-C ports to refuel mobile phones, tablets, and more
- Ready to fast charge compatible devices with Power Delivery (PD) via Type-C and QC3.0 via USB Type-A* †
- Includes attachable EU, UK, and AU plug adapters for charging compatibility in more than 150 countries
- Foldable plug (US version only) snaps out to charge and folds back in for condensed storage
- Compact form factor ensures maximum portability as well as an outlet fit that won't interfere with space for other chargers
- Safety measures including over voltage protection, over current protection, short circuit protection, and UL94V0 provide total protection for you and your devices
- High-quality construction extends the charger's life and improves overall performance

* Only one device may be connected to the charger at a time in order for fast charging to be enabled

† PD is supported by Android-based and iOS-based devices, while QC3.0 is only supported by Android-based devices (excluding some Huawei and OPPO models)



Specifications

- Total Power Output: 20W
- Input: AC100-240V, 50/60Hz Max 0.5A
- Output: USB (USB Type-A): 5V=3A, 9V=2A, 12V=1.5A ; Type-C: 5V=3A, 9V=2.22A, 12V=1.5A ; USB +Type-C: 5V=3.1A (max.)
- Dimensions: 42.7mm x 41.3mm x 29.0mm
- Weight: 96g
- Material: PC (UL94V0 Grade)
- Color: White
- Available Interface (Output): USB Type-A (x1), Type-C (x1)
- Available Interface (Input): US (with EU, UK, and AU Plug Adapters)
- Operating Temperature: 0°C - 40°C
- Protection: Over-Voltage Protection, Over-Current Protection, Short-Circuit Protection, Surge Protection, Flame-Retardant (UL94V0 Grade)
- Certification: ETL, PSE, BSMI, CE, FCC
- Warranty: 1 year